

High-Pressure Cleaner Dynajet 500th



Dynajet 500th

The top model in the Dynajet 500th series is high on performance: 500 bar max. pressure and a water flow of up to 30 l/min.

Using water at a temperature of 130°C, the Dynajet 500th has extraordinary cleaning powers – achieving a degree of soil removal for which you would normally require much more powerful machines.

PM Putzmeister
Mörtelmaschinen

... gives you just that little bit extra

2



Typical for the Dynajet 500th – the TARGA design featuring a practical separation of working area (blue hood) and engine compartment (grey hood).



General

A cleaner can never be powerful enough! And professional cleaning companies, in particular, should be able to rely on a machine with plenty of reserves. And one that can be used under extreme conditions.

Here, too, is the starter button to put the 32 KW diesel into action, the robust unit supplying the Dynajet 500th with constant and sufficient power.

But not only the motor is on a large scale – the water tank holds up to an amazing 1000 litres (!) which means you can clean at maximum efficiency for more than half an hour.

The Dynajet 500th is nevertheless constructed on a single axle (a unique feature in this class of machine!) which makes it extraordinarily manoeuvrable and easy to position on-site.

The Dynajet 500th with its high efficiency, modern design and user-friendliness makes it the high-pressure cleaner for the professionals – it simply has just that little bit extra of everything.

3



For all its high-power qualities, the Dynajet 500th remains a compact and very manoeuvrable machine – here seen in comparison with the 350th.



Operation

The 500th is a typical high-pressure cleaner from the Dynajet[®]-series. Just like its kid brother, the Dynajet 350th, it is built in the characteristic TARGA design which means that engine compartment and operating area are separated and can be accessed separately.

Advantage: the 500th is quieter as the hood is closed during operation.

In addition, the motor parts are protected from soiling and mal-operation – an absolute plus for tool and plant hire companies.

Everything you need for operation can be found beneath the blue hood where the high-pressure hoses and water hoses are e.g. coiled onto 2 rollers. The central element, however, is the control cabinet with an integrated control system comprising all the displays and operating elements such as the temperature display and emergency shut-down switch etc.

Technical Data

Water pressure	max. 500 bar
Water flow	15-30 l / min
Water temperature*	max. 130° C
Water tank	1,000 l
Diesel engine	3-cyl., 32 kW
Weight (empty)**	env. 1,470 kg
Dimensions (l x w x h)	365 x 210 x 210 cm

Part no. 500th 111 490.000

4



The heart of the Dynajet 500th: a robust 32 KW diesel engine and the high-performance combustor.

■ Your Putzmeister Partner

- **Mixing-, worm- and piston pumps for plaster and mortar**
- **Conveyors for floor-screed**
- **Professional high pressure cleaners**



*This data depends on the delivery output. **This data depends on the equipment. Subject to technical alterations. © 2002 by Putzmeister Mörtelmaschinen GmbH · All rights reserved · (1.50205 Pe).