


# Stationary pump BSA 702<sup>D</sup>



The small great multi-talent for shotcrete, floor-screed and fine concrete



Shotcreting

**Shotcreting, placing floor-screed, pumping concrete – the new, compact trailer concrete pump is a real multi-talent**

The small, light-weight and powerful trailer concrete pump to pump anhydrite cement and cementite, floor-screed as well as fine concrete with grain up to 16 mm. Ideal for shotcreting, grouting mortar and for concreting tasks with up to 16 mm grain.

The S transfer tube with automatic sealing effect allows pump pressures up to 70 bar, and is leak-proof even with slurries and water. Thanks to the automatic ring at the S-pipe, any wear that may occur is automatically compensated for.



Floor-screed



Fine concrete



The plastic bonnet can be supplied in its own individual colour (extra price)

## BSA 702<sup>D</sup> – the compact trailer concrete pump with S-transfer tube

- Piston pump with diesel-hydraulic drive mounted in steel frame, with T-chassis and standard overrun brakes
- Permissible for up to 80 km/h
- Plastic engine bonnet and TARGA strap cover the engine and provide good sound-insulation
- Concrete hopper with agitator, foldable 30 mm safety grid, hydraulic safety cut-off of the agitator when grid is opened
- Floor flap to empty and clean, as well as easy access to the wear parts on the agitator
- Double piston pump with hard-chromed pump cylinders and water box situated between the drive and pump cylinders, to flush the piston and cool the oil
- Exchange of pistons possible via the water box
- Electric control of pump and S-pipe
- Pump output can be manually set infinitely variably
- Central lubricating strip
- Pressure pipe transition pieces 100 – 4°

### Standard equipment:


Piston pump as roadworthy trailer with TÜV permit, medium-cooled Diesel engine, connection 4.5" SK, clamp couplings with seal, standard accessories and tools, operating instructions and spare parts list



The plastic bonnet that opens widely and the foldable hopper allow easy access to all parts, and make service and maintenance simple

### Technical data

Pump	Hydraulic double piston pump
Output (théor.)	20 m <sup>3</sup> /h
Conveying pressure (théor.)	70 bar
Delivery cylinder Ø / stroke	150 mm / 700 mm
Max. grain	16 mm
Drive	Deutz 3-cylinder Diesel F3M 2011 34 kW at 2600 rpm
Hopper / volume	TS 300 / 250 l
Pressure outlet	4.5" SK with reduction piece to 4" SK
Filling height	approx. 1,000 mm
Chassis / weight	F 80 / 1,900 kg
Unladen weight	1,860 kg
Dimensions (L/W/H)	4,200 mm / 1,460 mm / 1,600 mm



### Putzmeister Products and Services:

- PM-Concrete Pumps
- PM-Systems Engineering PAT
- PM-Telebelt
- PM-Mörtelmaschinen GmbH
- PM-Dynajet High Pressure Cleaners
- PM-Services
- PM-Concrete Project Division CPD
- PM-Consulting and Data Technology PCD
- PM-Akademie GmbH



Putzmeister AG  
 Max-Eyth-Str. 10 · D-72631 Aichtal  
 P.O.Box 21 52 · D-72629 Aichtal  
 Tel. + 49 (71 27) 599-0  
 Fax + 49 (71 27) 599-520  
<http://www.putzmeister.de>  
 E-mail: [pmw@pmw.de](mailto:pmw@pmw.de)